

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations Revision Date: 01/25/2016 Date of issue: 01/25/2016

Version: 1.0

## **SECTION 1: IDENTIFICATION**

# 1.1. Product Identifier

Product Form: Mixture

Product Name: Agetech™ Protectant

**Document Code: SDS217** 

### 1.2. Intended Use of the Product

Use of the substance/mixture: Coating to protect rubber from direct sunlight or outdoor weathering.

### 1.3. Name, Address, and Telephone of the Responsible Party

#### Company

Blair Rubber Company 5020 Panther Pkwy Seville, OH 44273 T 800-321-5583 blairrubber.com

### 1.4. Emergency Telephone Number

Emergency Number : 800-424-9300 (CHEMTREC), 202-483-7616 (International)

# **SECTION 2: HAZARDS IDENTIFICATION**

### 2.1. Classification of the Substance or Mixture

#### **GHS-US classification**

Flam. Liq. 2	H225
Skin Irrit. 2	H315
Skin Sens. 1	H317
Repr. 2	H361
STOT SE 3	H336
STOT RE 2	H373
Asp. Tox. 1	H304
Aquatic Acute 1	H400
Aquatic Chronic 1	H410
	_

Full text of hazard classes and H-statements: see section 16

## 2.2. Label Elements

**GHS-US Labeling** 

Hazard Pictograms (GHS-US)



GH507





Signal Word (GHS-US) : Danger

Hazard Statements (GHS-US) : H225 - Highly flammable liquid and vapor.

H304 - May be fatal if swallowed and enters airways.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction. H336 - May cause drowsiness or dizziness.

H361 - Suspected of damaging fertility or the unborn child.

H373 - May cause damage to organs through prolonged or repeated exposure

(Inhalation).

H400 - Very toxic to aquatic life.

 $\ensuremath{\mathsf{H410}}$  - Very toxic to a quatic life with long lasting effects.

Precautionary Statements (GHS-US) : P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from extremely high or low temperatures, ignition sources, and

incompatible materials. - No smoking. P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical, ventilating, and lighting equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

01/25/2016 EN (English US) 1/7

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P260 - Do not breathe vapors, mist, or spray.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P272 - Contaminated work clothing must not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, protective clothing, and eye protection.

P301+P310 - If swallowed: Immediately call a poison center or doctor.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P314 - Get medical advice/attention if you feel unwell.

P321 - Specific treatment (see section 4 on this SDS).

P331 - Do NOT induce vomiting.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P370+P378 - In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide ( $CO_2$ ), water to extinguish.

P391 - Collect spillage.

P403+P233+P235 - Store in a well-ventilated place. Keep container tightly closed. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

#### 2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

### 2.4. Unknown Acute Toxicity (GHS-US)

No data available

# **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

## 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product Identifier	%
Alkanes, C5-8	(CAS No) 101316-46-5	66.67
Antioxidant	(CAS No) Proprietary	15 - 25
Antioxidant	(CAS No) Proprietary	10 - 15

The specific chemical identity and/or exact percentage of composition has been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200].

Full text of H-phrases: see section 16

### **SECTION 4: FIRST AID MEASURES**

#### 4.1. Description of First Aid Measures

**First-aid Measures General**: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**First-aid Measures After Inhalation**: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

**First-aid Measures After Skin Contact**: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists. Wash contaminated clothing before reuse.

**First-aid Measures After Eye Contact**: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

**First-aid Measures After Ingestion**: Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

# 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms/Injuries:** Causes skin irritation. Skin sensitization. May cause drowsiness and dizziness. May be fatal if swallowed and enters airways. There are potential chronic health effects to consider.

01/25/2016 EN (English US) 2/7

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Symptoms/Injuries After Inhalation:** High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

**Symptoms/Injuries After Skin Contact:** Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

**Symptoms/Injuries After Ingestion:** Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury. **Chronic Symptoms:** Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure via inhalation.

## 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

## **SECTION 5: FIRE-FIGHTING MEASURES**

#### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>). Water may be ineffective but water should be used to keep fire-exposed container cool.

Unsuitable Extinguishing Media: Do not use a heavy water stream. A heavy water stream may spread burning liquid.

#### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Highly flammable liquid and vapor. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors.

**Explosion Hazard:** May form flammable or explosive vapor-air mixture.

**Reactivity:** Reacts violently with strong oxidizers. Increased risk of fire or explosion.

### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection. **Other Information:** Do not allow run-off from fire fighting to enter drains or water courses.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures**: Do not get in eyes, on skin, or on clothing. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges. Do not breathe vapor, mist or spray.

# 6.1.1. For Non-emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE). **Emergency Procedures:** Evacuate unnecessary personnel. Stop leak if safe to do so.

### 6.1.2. For Emergency Responders

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Eliminate ignition sources. Ventilate area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

# 6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment. Collect spillage.

### 6.3. Methods and Material for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools.

### 6.4. Reference to Other Sections

See Heading 8. Exposure controls and personal protection. See Section 13, Disposal Considerations.

# **SECTION 7: HANDLING AND STORAGE**

# 7.1. Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable.

**Precautions for Safe Handling:** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Take precautionary measures against static discharge. Use only non-sparking tools. Avoid contact with eyes, skin and clothing. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing. Do NOT breathe (vapor, mist, spray).

01/25/2016 EN (English US) 3/7

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations. Take action to prevent static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.

**Storage Conditions:** Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store in a well-ventilated place. Keep container tightly closed. Keep in fireproof place.

Incompatible Products: Strong acids. Strong oxidizers.

### 7.3. Specific End Use(s)

Coating to protect rubber from direct sunlight or outdoor weathering.

# **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

### 8.2. Exposure Controls

**Appropriate Engineering Controls** 

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosionproof equipment.

**Personal Protective Equipment** 

: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear

respiratory protection.









**Materials for Protective Clothing** 

: Chemically resistant materials and fabrics. Wear fire/flame resistant/retardant clothing.

Hand Protection Eye Protection : Wear protective gloves.: Chemical safety goggles.

**Skin and Body Protection** 

: Wear suitable protective clothing.

Respiratory Protection

: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

# 9.1. Information on Basic Physical and Chemical Properties

Physical State : Liquid

Appearance : Clear, amber
Odor : Solvent

Odor Threshold: No data availablepH: No data availableEvaporation Rate: No data availableMelting Point: No data availableFreezing Point: No data available

**Boiling Point** : 257 - 303 °F (125 - 151 °C)

Flash Point : No data available
Auto-ignition Temperature : No data available
Decomposition Temperature : No data available
Flammability (solid, gas) : No data available
Vapor Pressure : No data available
Relative Vapor Density at 20 °C : Heavier than air

Specific Gravity : 0.87

01/25/2016 EN (English US) 4/7

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Solubility** : Insoluble

Partition Coefficient: N-Octanol/Water: No data availableViscosity: No data available

Non-Vol (W/W) : 25 - 30

9.2. Other Information

VOC content : 4.6 lbs./gal.

### **SECTION 10: STABILITY AND REACTIVITY**

- 10.1. Reactivity: Reacts violently with strong oxidizers. Increased risk of fire or explosion.
- 10.2. Chemical Stability: Extremely flammable liquid and vapor. May form flammable or explosive vapor-air mixture.
- **10.3.** Possibility of Hazardous Reactions: Hazardous polymerization will not occur.
- **10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.
- 10.5. Incompatible Materials: Strong acids. Strong oxidizers.
- 10.6. Hazardous Decomposition Products: Thermal decomposition generates: Carbon oxides (CO, CO<sub>2</sub>). Nitrogen oxides.

# **SECTION 11: TOXICOLOGICAL INFORMATION**

# 11.1. Information On Toxicological Effects

Acute Toxicity: Not classified

Antioxidant	
LD50 Oral Rat	2100 mg/kg
Antioxidant	
LD50 Oral Rat	893 mg/kg
LD50 Dermal Rabbit	> 7940 mg/kg

**Skin Corrosion/Irritation:** Causes skin irritation. **Serious Eye Damage/Irritation:** Not classified

**Respiratory or Skin Sensitization:** May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

**Reproductive Toxicity:** Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity (Single Exposure): May cause drowsiness or dizziness.

**Specific Target Organ Toxicity (Repeated Exposure):** May cause damage to organs through prolonged or repeated exposure (Inhalation).

**Aspiration Hazard:** May be fatal if swallowed and enters airways.

**Symptoms/Injuries After Inhalation:** High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

**Symptoms/Injuries After Skin Contact:** Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

**Symptoms/Injuries After Ingestion:** Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury. **Chronic Symptoms:** Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure via inhalation.

## **SECTION 12: ECOLOGICAL INFORMATION**

## 12.1. Toxicity

**Ecology - General** : Very toxic to aquatic life with long lasting effects.

Antioxidant	
LC50 Fish 1	0.4 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	0.51 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	0.028 mg/l (Exposure time: 96 h - Species: Oryzias latipes [flow-through])

# 12.2. Persistence and Degradability

Agetech™ Protectant	
Persistence and Degradability	May cause long-term adverse effects in the environment.

### 12.3. Bioaccumulative Potential

Agetech™ Protectant	
Bioaccumulative Potential	Not established.
	•

01/25/2016 EN (English US) 5/7

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Antioxidant	
BCF fish 1	(bioaccumulation expected)
Log Pow	5.4

**12.4. Mobility in Soil** No additional information available.

12.5. Other Adverse Effects

**Other Information** : Avoid release to the environment.

### **SECTION 13: DISPOSAL CONSIDERATIONS**

### 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, and international regulations.

Additional Information: Handle empty containers with care because residual vapors are flammable.

**Ecology – Waste Materials:** Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

## **SECTION 14: TRANSPORT INFORMATION**

## 14.1. In Accordance with DOT

Proper Shipping Name : PETROLEUM DISTILLATES, N.O.S. (Contains hydrocarbon mixture C5-C8 aliphates; proprietary

aromatic amine)

Hazard Class : 3

Identification Number : UN1268

Label Codes : 3
Packing Group : II

Marine Pollutant : Marine pollutant

ERG Number : 128

14.2. In Accordance with IMDG

Proper Shipping Name : PETROLEUM DISTILLATES, N.O.S. (Contains hydrocarbon mixture C5-C8 aliphates; proprietary

aromatic amine)

Hazard Class : 3

Identification Number : UN1268

Packing Group : II
Label Codes : 3
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E

Marine Pollutant : Marine pollutant



**Proper Shipping Name** : PETROLEUM DISTILLATES, N.O.S. (Contains hydrocarbon mixture C5-C8 aliphates; proprietary

aromatic amine)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Packing Group : ||

Identification Number : UN1268

Hazard Class : 3 Label Codes : 3 ERG Code (IATA) : 3H



# **SECTION 15: REGULATORY INFORMATION**

# 15.1 US Federal Regulations

Agetech™ Protectant		
SARA Section 311/312 Hazard Classes	Fire hazard	
	Immediate (acute) health hazard	
	Delayed (chronic) health hazard	
Antioxidant		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Antioxidant		

**15.2 US State Regulations** Neither this product nor its chemical components appear on any US state lists.

01/25/2016 EN (English US) 6/7

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

# SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Revision Date** : 01/25/2016

Other Information : This document has been prepared in accordance with the SDS

requirements of the OSHA Hazard Communication Standard 29 CFR

1910.1200.

### **GHS Full Text Phrases:**

Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Asp. Tox. 1	Aspiration hazard Category 1
Flam. Liq. 2	Flammable liquids Category 2
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)

01/25/2016 EN (English US) 7/7