

## MJ-3500 JOINT TAPE

MARSEAL® corrosion resistant sheet membrane incorporating DuPont Elvaloy® resin, reinforced with dispersed polyester fibers. It is used in conjunction with MARSEAL® Structural Sealant, to seal and waterproof problematic expansion/contraction joints in secondary containment areas, sumps, water treatment facilities, tunnels, or anywhere joints require sealing.

### SPECIFICATIONS

**AVAILABLE SIZES:**

75-mil membrane supplied in 50' rolls.

#### TYPICAL PHYSICAL PROPERTIES

Hardness	Shore A	85A +/-5
Elongation	ASTM D412	170%
Tensile Strength at Yield	ASTM D412	1500lbs/in <sup>2</sup>
Tear Strength	ASTM D624	330 ppi
Low Temperature Flexibility	ASTM D2137	Pass
Water Absorption	ASTM D471	<0.1%
Water Vapor Transmission	ASTM E96	0.065 grains/h-ft <sup>2</sup>



**DISCLAIMER:**

The above guidelines are based on general industry practices and not applicable to all installations. Please contact Blair Rubber Company for specific application instructions. Application methods shall conform to Blair Rubber Company instructions contained in the Engineering & Applicator manual. Deviations from the specifications must be approved in writing by Blair Rubber Company. Data values are approximate and may vary based on installation techniques and atmospheric conditions. As such, data values should be used as general guidelines and are not a legally binding warranty of product characteristics. This document is copyright to and the intellectual property of Blair Rubber Company and may not be copied or distributed without prior consent.