

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: Enduraflex™ CU535BEP, EP, VE518BEP; LE5P600 Slab Stock

Document Code: SDS225

Family: Rubber Lining

1.2. Intended Use of the Product

Use of the substance/mixture: EPDM Rubber Lining. For Professional Use Only.

1.3. Name, Address, and Telephone of the Responsible Party

Company

Blair Rubber Company

5020 Enterprise Parkway

Seville, OH 44273

T 330-769-5583

blairrubber.com

1.4. Emergency Telephone Number

Emergency Number : 800-424-9300 (CHEMTREC), 202-483-7616 (International)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

Classification (GHS-US)

Skin Sens. 1 H317

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Warning

Hazard Statements (GHS-US)

: H317 - May cause an allergic skin reaction.

Precautionary Statements (GHS-US)

: P261 - Avoid breathing dust, fumes from decomposition, vapors from decomposition.

P272 - Contaminated work clothing must not be allowed out of the workplace.

P280 - Wear eye protection, protective clothing, protective gloves.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P321 - Specific treatment (see Section 4).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P501 - Dispose of contents/container according to local, regional, national, and international regulations.

2.3. Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. When heated to decomposition, emits toxic fumes. May cause an allergic reaction in sensitive individuals. Contains chemicals with hazards that are associated with their dust and usual forms. The hazards associated with these chemicals are not bioavailable under normal conditions of use due to the compounds being polymer bound.

2.4. Unknown Acute Toxicity (GHS-US)

54.35 percent of the mixture consists of ingredient(s) of unknown acute toxicity.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Enduraflex™ CU535BEP, EP, VE518BEP; LE5P600 Slab Stock

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product Identifier	%
Carbon black	(CAS No) 1333-86-4	5.0 – 10.0
Plasticizer #1	(CAS No) Proprietary	3.0 – 7.0
Plasticizer #2	(CAS No) Proprietary	3.0 – 7.0
Activator #1	(CAS No) Proprietary	1.0 – 5.0
Crosslinker #1	(CAS No) Proprietary	0.1 – 1.0
Process Aid #13	(CAS No) Proprietary	0.1 – 1.0
Accelerator #1	(CAS No) Proprietary	0.1 – 1.0
Activator #12	(CAS No) Proprietary	0.1 – 1.0
Activator #16	(CAS No) Proprietary	0.1 – 1.0
Antidegradant #5	(CAS No) Proprietary	0.1 – 0.5

The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret [29 CFR 1910.1200].

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

First-aid Measures After Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

First-aid Measures After Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

First-aid Measures After Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

First-aid Measures After Ingestion: Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/Injuries: May cause an allergic reaction in sensitive individuals.

Symptoms/Injuries After Inhalation: When heated, material emits irritating fumes.

Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: Fumes from thermal decomposition may cause eye irritation.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide, foam.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Other Information: Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid prolonged contact with eyes, skin and clothing. Do not breathe fumes from fires or vapors from decomposition.

Enduraflex™ CU535BEP, EP, VE518BEP; LE5P600 Slab Stock

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.1. For Non-emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Responders

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Sweep or vacuum the product to recover it.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely.

6.4. Reference to Other Sections

See Heading 8. Exposure controls and personal protection. Concerning disposal elimination after cleaning, see item 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: When heated to decomposition, emits toxic fumes.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Products: Strong acids. Strong bases. Strong oxidizers.

7.3. Specific End Use(s)

EPDM Rubber Lining. For Professional Use Only.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), or OSHA (PEL).

Carbon black (CAS No) 1333-86-4		
USA ACGIH	ACGIH TWA (mg/m ³)	3 mg/m ³ (inhalable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	3.5 mg/m ³ 0.1 mg/m ³ (Carbon black in presence of Polycyclic aromatic hydrocarbons)
USA IDLH	US IDLH (mg/m ³)	1750 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	3.5 mg/m ³
Activator #1 (CAS No) Proprietary		
USA ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³ (respirable fraction)
USA ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³ (dust and fume)
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	10 mg/m ³ (fume)
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	15 mg/m ³ (dust)
USA IDLH	US IDLH (mg/m ³)	500 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³ (fume) 15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
Antidegradant #5 (CAS No) Proprietary		
USA ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³ (fume)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	2 mg/m ³ (fume)

8.2. Exposure Controls

Appropriate Engineering Controls

: Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.

Enduraflex™ CU535BEP, EP, VE518BEP; LE5P600 Slab Stock

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal Protective Equipment

: Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing

: Chemically resistant materials and fabrics.

Hand Protection

: Wear chemically resistant protective gloves.

Eye Protection

: Chemical goggles or safety glasses.

Skin and Body Protection

: Wear suitable protective clothing.

Respiratory Protection

: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

Consumer Exposure Controls

: Do not eat, drink or smoke during use.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Solid
Appearance	: Black
Odor	: No data available
Odor Threshold	: No data available
pH	: No data available
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: No data available
Flash Point	: 500 °F (260 °C)
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor Pressure	: No data available
Relative Vapor Density at 20 °C	: No data available
Specific Gravity	: 1.13
Density	: 1.54 lb/ft ³ (1/4" thk)
Solubility	: Insoluble in water
Partition Coefficient: N-octanol/water	: No data available
Viscosity	: No data available

9.2. Other Information

No additional information available.

SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2. Chemical Stability:** Stable at standard temperature and pressure.
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures. Ignition sources. Incompatible materials.
- 10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers.
- 10.6. Hazardous Decomposition Products:** Carbon oxides (CO, CO₂). Sulfur oxides. Oxides of zinc. Thermal decomposition generates hydrochloric acid, hydrocarbons, soot, toxic gases.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information On Toxicological Effects

Acute Toxicity: Not classified

Carbon black (CAS No) 1333-86-4	
LD50 Oral Rat	> 8000 mg/kg
Plasticizer #1 (CAS No) Proprietary	
LD50 Oral Rat	> 5000 mg/kg

Enduraflex™ CU535BEP, EP, VE518BEP; LE5P600 Slab Stock

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

LD50 Dermal Rat	> 2000 mg/kg
LC50 Inhalation Rat	2.18 mg/l/4h
Plasticizer #2 (CAS No) Proprietary	
LD50 Oral Rat	> 5000 mg/kg
Activator #1 (CAS No) Proprietary	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rat	> 2000 mg/kg
Crosslinker #1 (CAS No) Proprietary	
LD50 Oral Rat	> 3000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 9.23 mg/l/4h
Accelerator #1 (CAS No) Proprietary	
LD50 Oral Rat	690 mg/kg
LD50 Dermal Rat	> 2000 mg/kg
Activator #12 (CAS No) Proprietary	
LD50 Oral Rat	> 10000 mg/kg
Process Aid #13 (CAS No) Proprietary	
LD50 Oral Rat	47000 mg/kg
LD50 Dermal Rabbit	> 20 ml/kg
Activator #16 (CAS No) Proprietary	
LD50 Dermal Rabbit	> 7940 mg/kg
Antidegradant #5 (CAS No) Proprietary	
LD50 Oral Rat	> 3750 mg/kg
LD50 Dermal Rabbit	> 3600 mg/kg

Skin Corrosion/Irritation: Not classified

Serious Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Carbon black (CAS No) 1333-86-4	
IARC group	2B
Activator #16 (CAS No) Proprietary	
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity.

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: When heated, material emits irritating fumes.

Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: Fumes from thermal decomposition may cause eye irritation.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Carbon black (CAS No) 1333-86-4	
EC50 Daphnia 1	5600 mg/l (Exposure time: 24 h - Species: Daphnia magna)
Plasticizer #1 (CAS No) Proprietary	
LC50 Fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Plasticizer #2 (CAS No) Proprietary	
LC50 Fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)

Enduraflex™ CU535BEP, EP, VE518BEP; LE5P600 Slab Stock

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Activator #1 (CAS No) Proprietary	
LC50 Fish 1	780 µg/l (Exposure time: 96 h - Species: Pimephales promelas)
EC50 Daphnia 1	0.122 mg/l
NOEC chronic fish	0.026 mg/l (Species: Jordanella floridae)
Crosslinker #1 (CAS No) Proprietary	
LC50 Fish 1	866 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
EC50 Daphnia 1	736 mg/l
LC 50 Fish 2	14 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
Accelerator #1 (CAS No) Proprietary	
LC50 Fish 1	4.2 - 6.8 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [semi-static])
EC50 Daphnia 1	1.4 - 1.8 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	1.8 - 3.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
Activator #12 (CAS No) Proprietary	
LC50 Fish 1	4.4 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	1.3 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
Activator #16 (CAS No) Proprietary	
LC50 Fish 1	1.32 - 2.73 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	4.1 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	0.42 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])

12.2. Persistence and Degradability No additional information available.

12.3. Bioaccumulative Potential

Accelerator #1 (CAS No) Proprietary	
Log Pow	1.17
Activator #16 (CAS No) Proprietary	
BCF fish 1	< 0.8
Log Pow	2.3 - 2.5

12.4. Mobility in Soil No additional information available.

12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international regulations.

SECTION 14: TRANSPORT INFORMATION

14.1. In Accordance with DOT Not regulated for transport.

14.2. In Accordance with IMDG Not regulated for transport.

14.3. In Accordance with IATA Not regulated for transport.

SECTION 15: REGULATORY INFORMATION

15.1 US Federal Regulations

Enduraflex™ CU535BEP, EP, VE518BEP; LE5P600 Slab Stock	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
Carbon black (CAS No) 1333-86-4	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Plasticizer #1 (CAS No) Proprietary	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Plasticizer #2 (CAS No) Proprietary	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Activator #1 (CAS No) Proprietary	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Crosslinker #1 (CAS No) Proprietary	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

Enduraflex™ CU535BEP, EP, VE518BEP; LE5P600 Slab Stock

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Accelerator #1 (CAS No) Proprietary	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Activator #12 (CAS No) Proprietary	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Process Aid #13 (CAS No) Proprietary	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Activator #16 (CAS No) Proprietary	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on United States SARA Section 313	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - Emission Reporting	1.0 %
Antidegradant #5 (CAS No) Proprietary	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2 US State Regulations

Carbon black (CAS No) 1333-86-4	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
Carbon black (CAS No) 1333-86-4	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances	
U.S. - Pennsylvania - RTK (Right to Know) List	
Plasticizer #2 (CAS No) Proprietary	
U.S. - Massachusetts - Right To Know List	
Activator #1 (CAS No) Proprietary	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
U.S. - Pennsylvania - RTK (Right to Know) List	
Crosslinker #1 (CAS No) Proprietary	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	
Activator #16 (CAS No) Proprietary	
U.S. - New Jersey - Right to Know Hazardous Substance List	
Antidegradant #5 (CAS No) Proprietary	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date	: 07/05/2019
Other Information	: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Skin Sens. 1	Skin sensitization Category 1
H317	May cause an allergic skin reaction

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)