



# TERMINATION BARS

MARSEAL® used as mechanical attachment devices for anchoring MARSEAL® membranes at termination points.

<b>MARSEAL® TERMINATION BAR - FLAT (MEMBRANE EDGE DOWN)</b>	
Material	Extruded aluminum without sharp edges.
Dimensions	1" wide x .090" thick x 5' length.
Holes	1/4" x 3/8" slotted holes 6" centers.
Shipping Weight	.625 lbs. / bar.

<b>MARSEAL® TERMINATION BAR - CAULK LIP (MEMBRANE EDGE UP)</b>	
Material	Extruded aluminum without sharp edges.
Dimensions	1" wide x .090" thick x 5' length, with 45° caulk lip on one side of bar.
Holes	1/4" x 3/8" slotted holes 6" centers.
Shipping Weight	.625 lbs. / bar.



**DISCLAIMER:**

The above guidelines are based on general industry practices and not applicable to all installations. Please contact Blair Rubber Company for specific application instructions. Application methods shall conform to Blair Rubber Company instructions contained in the Engineering & Applicator manual. Deviations from the specifications must be approved in writing by Blair Rubber Company. Data values are approximate and may vary based on installation techniques and atmospheric conditions. As such, data values should be used as general guidelines and are not a legally binding warranty of product characteristics. This document is copyright to and the intellectual property of Blair Rubber Company and may not be copied or distributed without prior consent.