

YELLOW WALKWAY

MARSEAL® PVC-based matting with an aggressive, slip-resistant tread design. Easy to install on any **MARSEAL®** membrane. Can withstand heavy duty foot and equipment traffic. Resistant to mild acids, caustics, and hydrocarbon-based derivatives.

SPECIFICATIONS

AVAILABLE SIZES:

30" wide by 40' long (100 sq. feet per roll.)

TYPICAL PHYSICAL PROPERTIES

Thickness	3/16" (5mm)
Color	Yellow

APPLICATOR NOTES

1. Surface should be clean and smooth. Vacuum or brush off all dirt, loose objects, etc.
2. Yellow Walkway, when used over a floor lined with M-4000 Corrosion Resistant Lining can be spot-hot air welded directly to membrane surface to hold walkway in place.
3. When used over M-8000 or exposed or coated concrete, the use of Structural Sealant is recommended. Apply 1/4" beads of Structural Sealant on 6-inch centers to a clean surface with a caulking gun.
4. Place Yellow Walkway into wet Structural Sealant and roll to insure a tight bond.

DISCLAIMER:

The above guidelines are based on general industry practices and not applicable to all installations. Please contact Blair Rubber Company for specific application instructions. Application methods shall conform to Blair Rubber Company instructions contained in the Engineering & Applicator manual. Deviations from the specifications must be approved in writing by Blair Rubber Company. Data values are approximate and may vary based on installation techniques and atmospheric conditions. As such, data values should be used as general guidelines and are not a legally binding warranty of product characteristics. This document is copyright to and the intellectual property of Blair Rubber Company and may not be copied or distributed without prior consent.